## MINING CABLE PROTECTION

## STRAIN RELIEF CLAMPS

Patton & Cooke's two types of strain relief clamps eliminate strain on the cable connections at the coupler/enclosure interface on electric shovels, drills, LHDs, jumbos, junction boxes or cable supports. Strain relief clamps also support cables in vertical shaft and pole suspension applications.

## **FEATURES:**

- Eliminates strain on the cable connections at the coupler/enclosure interface on electric shovels, drills, LHDs, jumbos, junction boxes or cable supports
- Supports a cable in vertical shaft and pole suspension applications
- Standard 11W-010 series made of thick, black polyurethane and using galvanized hardware and wire rope, the strain relief clamp is designed to prevent cable jacket damage and to withstand the tough use typical in mining, construction and utility applications
- Standard 11W-010 series strain relief clamp is available in twelve sizes, covering a cable diameter range of 0.625-3.625" (16-92 mm). Larger sizes are available on request
- The HD clamp is a single design covering a wide cable range

Standard	
Catalogue Number	Cable Diameter Range
11W-010-A	0.625" - 0.875"
11W-010-B	0.876" - 1.125"
11W-010-C	1.126" - 1.375"
11W-010-D	1.376" - 1.625"
11W-010-E	1.626" - 1.875"
11W-010-F	1.876" - 2.125"
11W-010-G	2.126" - 2.375"
11W-010-H	2.376" - 2.625"
11W-010-J	2.626" - 2.875"
11W-010-K	2.876" - 3.125"
11W-010-L	3.126" - 3.375"
11W-010-M	3.376" - 3.625"

HEAVY DUTY	
Catalogue Number	Cable Diameter Range
11W-011-AL	2.1875" - 2.875"









